

Security Camera / Access Control Power Supply (SMPS)



Application: 1 Camera

I/P: 170-265 V AC, 50 Hz Open Ended Wire
 O/P: 12 V DC@ 500 mA Open Ended Wire
 Protections: UV/OV, Short Cct. & Overload
 80 LX 55 W X 21 H mm Weight:48 gms
 Max Power: 6 Watt Model: ADP12500

Application: 2 Camera

I/P: 100-265 V AC, 50 Hz Two/Three pin
 O/P: 12 V DC@ 1 A Casio plug
 Protections: UV/OV, Short Cct. & Overload
 62 LX49 WX35/62 D mm Weight:96 gms
 Max Power: 12 Watt
 Model: ADP1201



Application: 3/4 Camera

I/P: 170-265 V AC, 50 Hz Two pin Cord
 O/P: 12 V DC@ 2 A Open Ended Wire
 Protections: UV/OV, Short Cct. & Overload
 95 LX 60 W X 50 D mm Weight: 190 gms
 Max Power: 24 Watt
 Model: ADP24W12

Application: 5/6 Camera

I/P: 100-265 V AC, 50 Hz Two pin Cord
 O/P: 12 V DC@ 3 A Open Ended Wire
 Protections: UV/OV, Short Cct. & Overload
 Max Power: 24 Watt
 120 X 65 W X 42 H mm Weight: 300 gms
 Max Power: 36 Watt Model: ADP36W12



Application: 8 to 10 Camera

I/P: 100-265 V AC, 50 Hz Connector
 O/P: 12 V DC@ 5 A Connector
 Protections: UV/OV, Short Cct. & Overload
 135 LX 75 W X 47 D mm Weight:435 gms
 Max Power: 60 Watt
 Model: CS1205/ CSDT1205

Application: 16 to 20 Camera

I/P: 170-265 V AC, 50 Hz Connector
 O/P: 12 V DC@ 10 A Connector
 Protections: UV/OV, Short Cct. & Overload
 160 L X 125 W X 55 H mm Weight: 850 gms
 Max Power: 120 Watt
 Model: CS1210



DVR Power Supply

I/P: 100-265 V AC, 50 Hz Cord
 O/P: 19 VDC@ 3.5A open wire
 Protections: UV/OV, Short Cct. & Overload Model: CS1903
 Max Power: 75 Watt
 L135 X 75 W X 80 H mm
 Max Power: 120 Watt



Battery Back Supply

I/P: 170-260 V AC
 Battery: 12 V/7 AH
 O/P: 5 V @ 1 A
 Backup : 12 Hrs
 Application: Access Control
 Model: CBB501



Linear Power Supply

I/P: 230 V AC
 O/P: 24 V AC @ 3Amps
 Size: 120x120x100 mm
 Model: LPS2403A








PESS Corporation

312, Shaniwar Peth, Siddhant Apt. Campus, PUNE.411030 (INDIA)
 Tel.91-20-2448 7774, 2448 3234 Fax : 91-20-24487774

Email: pess@vsnl.net sales@powersupplyindia.com

Website: www.powersupplyindia.com

SMPS for CCTV Application: GEN Series

<p>Application: 2 Dome Cameras / 1 IR Model: GEN121 I/P: 170-265 V AC, 50 Hz Three Pin Connector O/P: 12 V DC@ 1.0 A Two Pin Connector Protections: UV/OV, Short Cct. & Overload Indications: O/P On 90 L X 43 W X 33 D mm Weight: 60 gms Max Power: 12 Watts</p>	
	<p>Application: 4 Dome Cameras / 2 IR Model: GEN122 I/P: 170-265 V AC, 50 Hz Three Pin Connector O/P: 12 V DC@ 2.0 A Two Pin Connector Protections: UV/OV, Short Cct. & Overload Indications: O/P On 100 L X 58 W X 38 D mm Weight: 190 gms Max Power: 24 Watts</p>
<p>Application: 8 Dome Cameras/ 4 IR Model: GEN124 I/P: 170-265 V AC, 50 Hz Three Pin Connector O/P: 12 V DC@ 4.3 A Four Pin Connector Protections: UV/OV, Short Cct. & Overload Indication: O/P On 150 L X 90 W X 38 D mm Weight : 380 gms Max Power: 50 Watt</p>	
	<p>Application: 16 Dome Cameras/8 IR Model: GEN128 I/P: 170-265 V AC, 50 Hz Three Pin Connector O/P: 12 V DC@ 8.25A 4 Pin Connector Protections: UV/OV, Short Cct. & Overload Indication: O/P On 160L X 91 W X 40 D mm Weight: 480 gms Max Power: 100 Watt</p>
<p>Application: 32 Cameras Model: GEN1216 I/P: 170-265 V AC, 50 Hz Connector O/P: 12 VDC@ 16A , Connector Protections: UV/OV, Short Cct. & Overload 215 L X 115 W X 50 D mm Weight: 750 gms Max Power: 192 Watt</p>	
<p>PESS Corporation 312, Shaniwar Peth, Siddhant Apt. Campus, PUNE.411030 (INDIA) Tel.91-20-2448 7774, 2448 3234 Fax : 91-20-24487774 Email: pess@vsnl.net / pesscorporation@gmail.com Website:www.powersupplyindia.com Email2: sales@powersupplyindia.com</p>	

Power Supply (SMPS) for CCTV Multi O/P

Application: 2-3 Cameras

Model: IS1201P5T2
I/P: 170-265 V AC, 50 Hz Connector
O/P: 12 V DC@ 1.5 A Connector
Protections: UV/OV, Short Cct. & Overload
110 L X 50 W X 38 H mm
Weight: 230 gms
Max Power: 18 Watt



Application: 4-6 Cameras

Model: IS1203T5
I/P: 100-265 V AC, 50 Hz Connector
O/P: 12 V DC@ 3 A Connector
Protections: UV/OV, Short Cct. & Overload
127 L X 65 W X 45 H mm
Weight: 380 gms
Max Power: 36 Watt



Application: 6-8 Cameras

Model: IS1205T8
I/P: 100-265 V AC, 50 Hz Connector
O/P: 12 V DC@ 5A Connector
Protections: UV/OV, Short Cct. & Overload
140 L X 95 W X 50 H mm
Weight: 450 gms
Max Power: 60 Watt



Application: 6-8 Cameras

Model: CS1206T10
Max Power: 72 Watt
I/P: 170-265 V AC, 50 Hz Cord
O/P: 12 VDC@ 6A ,
10 O/P with Indication & Fuse protected
In case of Short Cct only single camera is off and other are in working condition.
Protections: UV/OV, Short Cct. & Overload
133 L X 180 W X 55 H mm
Weight: 890 gms

PSS Corporation

312, Shaniwar Peth, Siddhant Apt. Campus, PUNE.411030 (INDIA)
Tel.91-20-2448 7774, 2448 3234 Fax : 91-20-24487774
Email1: pess@vsnl.net / pesscorporation@gmail.com
Website:www.powersupplyindia.com
Email2: sales@powersupplyindia.com